


BusLED King bus side display specification



Physical Specifications

Usage	Outdoor
Physical Dimensions (LxHxD)	140" x 24" x 0.87"
Enclosure	3mm polycarbonate cover and Stainless-steel frame
Environmental	Operating Temp -30C to +75C
Weight	68kg approx
Power	27.6v DC existing supply 18 to 35v input voltage 75A max Average Power 550W
Display Specifications	
Image Display Area (W x H)	136" x 23"
Display Types	Displays static image, animation & full video
Video Resolution	576 x 96 pixels
LED Type	SMT2727
Pixel Pitch	6mm
Colour Spectrum	R: 620nm, G: 530nm, B: 470nm
Brightness	Over 5,000 nits

Cont....

Colour Depth	24 bit capture
Aspect Ratio	Variable
Refresh/Frame Rate	1920Hz/60Hz
Horizontal Viewing	140°
Comms Enclosure	
Usage	Indoor
Physical Dimensions (L x W x H)	15" x 11" x 7"
Enclosure	Powder coated steel enclosure
Weight	5Kg Approx.
Environmental	Operating Temp -20C to +75C IP53
Power	27.6v DC existing supply 18 to 35v input voltage 2A max
Built-in Computer	Embedded Media Player & integrated communications options - including 3G
Embedded safety	Standalone interlock monitoring system

www.motionledtechnology.com

Head Office +44 (0)20 8720 6504

hello@motionledtechnology.com

MotionLED
TECHNOLOGY